

00015360-072701

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, HIROSHI ISHII, a citizen of Japan residing at Kanagawa, Japan, HIROMI OKUBO, a citizen of Japan residing at Kanagawa, Japan and SHOGO ONEDA, a citizen of Japan residing at Chiba, Japan have invented certain new and useful improvements in

IMAGE PROCESSING DEVICE, IMAGE PROCESSING METHOD AND  
IMAGE FORMING APPARATUS

of which the following is a specification:-

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to an image processing device for performing image drawing processing according to image drawing instructions given by a host.

2. Description of the Related Art

In the related art, in an image processing device used in a printer or the like, in response to drawing instructions given by a host computer, a CPU interprets the drawing instructions, generates bitmap data to be sent to a printer engine, and stores it in a memory. The image processing device transfers the bitmap data stored in the memory to the printer engine by DMA transfer in accordance with operation of the printer engine, and, thereby, the printer engine prints out relevant image data.

In order to improve the processing speed of the image processing device, Japanese Laid-Open Patent Application No. 11-31052, for example, discloses a document processing system which divides document data into a plurality of sets of first interim data, distributes the respective ones of the plurality of sets of first interim data into a plurality of drawing units

0915360 072701

which can operate it in parallel, and convert the plurality of sets of first interim data into a plurality of sets of second interim data. Then, a combining unit combines the plurality of sets of second interim data in  
5 page unit, so as to generate image data which can be printed out. Thus, high speed processing can be achieved.

However, Japanese Laid-Open Patent Application No. 11-31052 does not disclose a configuration with  
10 regard to a case where the interim data is data obtained through data compression. However, image data for a size of A4 in 600 dpi of 8 bits for each color of RGB has a data amount of approximately 100 MB, for example, and, as a result, when this data is transferred from a  
15 host computer to a printer without compression, a considerable time is required for the transfer. In order to solve this problem, image data is transferred commonly after being appropriately compressed.

However, if thus-compressed image data is to  
20 be processed by the above-mentioned document processing system, the compressed image data should be decompressed first, then be divided into a plurality of sets of drawing instructions and corresponding image data, which are then distributed into the plurality of drawing units.  
25 Thus, the plurality of drawing units cannot perform the

0015360-072701

processing until the decompressing processing is finished, and, thereby, it is not necessarily possible to achieve high-speed image production processing.

5 SUMMARY OF THE INVENTION

An object of the present invention is to provide an image processing form by which the above-mentioned problems can be solved.

An image processing form according to the  
10 present invention includes:

a plurality of image production processing parts each of which generates drawing data for image drawing processing from image drawing instructions obtained through data compression;

15 a dividing part which divides the given image drawing instructions into a plurality of sets of image drawing instructions without decompressing them in such a manner that each set of image drawing instructions can be processed by any of the plurality of image producing  
20 processing part without referring to any other set of image drawing instructions; and

a distributing part which distributes the plurality of sets of image drawing instructions to the plurality of image production processing parts.

25 Thereby, it is possible to divide given image

0015360.072701

drawing instructions, obtained through data compression, into a plurality of sets of instructions to be performed by the plurality of image production processing parts in parallel, without previously decompressing them.

- 5 Accordingly, it is possible to hand over the given instructions to the image production processing parts rapidly in a form of divisions of image drawing instructions which can be directly processed by the image production processing parts in parallel. Thus, it
- 10 is possible to achieve high-speed image processing for providing drawing data used for forming a printed image, for example.

- Image data corresponding to the image drawing instructions to be processed may comprise image data
- 15 obtained through data compression such that the image data comprises a plurality of data blocks and each data block can be decompressed without referring to any other data block.

- Thereby, even in a case where image data to be
- 20 processed is image data obtained through data compression such that decompression of each line of image data needs another line thereof, it is possible to easily divide the given image data into a plurality of sets of image drawing instructions which can be
- 25 processed by the plurality of image production

00915350-072701

processing parts in parallel without previously  
decompressing it, as long as the division is made such  
that a division unit is a multiple of a number of lines  
included in each data block. Thus, it is possible to  
5 apply the present invention to image data obtained by  
various data compressing methods.

Other objects and further features of the  
present invention will become more apparent from the  
following detailed description when read in conjunction  
10 with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a block diagram of a general  
configuration of an image processing device in an  
15 embodiment of the present invention;

FIG. 2 illustrates operation of dividing given  
image data (image drawing instructions);

FIG. 3 illustrates operation of dividing given  
image drawing instructions into four sets of image  
20 drawing instructions, corresponding to the four regions  
of image shown in FIG. 2, performed by the image  
processing device shown in FIG. 1;

FIG. 4 shows a flow chart performed by the  
image processing device shown in FIG. 1; and

25 FIG. 5 illustrates an image forming apparatus

09915360.072701

which employs the image processing device shown in FIG.

1;

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5               FIGS. 1 through 5 illustrate one embodiment of the present invention.

FIG. 1 shows a block diagram illustrating a general configuration of an image processing device 1 in one embodiment of the present invention.

10              As shown in FIG. 1, the image processing device 1 includes a host I/F (interface) 2, a memory 3, an instruction dividing and distributing part 4, an engine I/F 5, and a plurality of image production processing parts 6a through 6n. The respective parts  
15 are mutually connected by a bus 7. This image processing device 1 may be used in an image forming apparatus such as a printer or the like.

To the host I/F , a host apparatus 10 such as a host computer is connected through a communication  
20 circuit 8 such as a network or a serial circuit. The host apparatus 10 produces image drawing instructions by using an image drawing instruction producing part 11 based on instructions given by a user, and transmits the thus-produced instructions to a printer or the like  
25 which employs the above-mentioned image processing

0015360-072701

device 1. In this occasion, the image drawing instruction producing part 11 of the host apparatus 10 compresses an image object by a predetermined compressing method such as a fixed length compressing method, and, then, transmits it to the printer or the like.

The host I/F 2 receives the image drawing instructions transmitted from the host apparatus 10 through the communication circuit 8, and writes them into the memory 3.

The memory 3 includes a RAM (Random Access Memory) or the like, and, stores therein the received image drawing instructions and other various data.

The instruction dividing and distributing part 4 reads the image drawing instructions from the memory 3, analyses the read image drawing instructions, determines whether to process these instructions separately after dividing into a plurality of sets of instructions or to process them collectively without dividing into a plurality of sets of instructions, and transfers the image drawing instructions to the plurality of image production processing parts 6a through 6n after dividing them or not dividing them accordingly.

Specifically, when the image drawing instructions read from the memory 3 are instructions for

00015360.072701



processing concerning an image object, and, an area to be processed or a data amount of the corresponding image object is larger than a predetermined reference value, the given image drawing instructions are divided into a plurality of sets of image drawing instructions as shown in FIG. 2, and the thus-divided sets of image drawing instructions are then distributed into the respective image production processing parts 6a through 6n, which then process the divided image drawing instructions and process them, respectively, separately.

However, when the image drawing instructions read from the memory 3 are instructions for processing concerning an image object, but, an area to be processed or a data amount of the corresponding image object is not larger than the predetermined reference value, the image drawing instructions are not divided into a plurality of sets of image drawing instructions, and the image drawing instructions are transferred to the respective image production processing parts 6a through 6n (or an appropriate one thereof) as they are.

As the image object is one transmitted after being compressed by the host apparatus 10 by the fixed length compressing method, for example, the instruction dividing and distributing part 4 can easily calculate a position at which image data corresponding to each

00000000.072701

region obtained through the division (see FIG. 2) is located in the image drawing instructions. As shown in FIG. 3, it is easy to produce image objects corresponding to the respective image drawing instructions obtained through the division.

Then, the image production processing parts 6a through 6n analyze the image drawing instructions given by the instruction dividing and distributing part 4, generate bitmap data (drawing data) which can be directly transferred to and processed by a printer engine (not shown in the figure), and transmit it to the printer engine through the engine I/F 5.

The engine I/F 5 to which the printer engine is connected performs communication of the bitmap data from the image production processing parts 6a through 6n to the printer engine, a control signal from the instruction dividing and distributing part 4 to the printer engine, a status signal from the printer engine to another part, and so forth.

FIG. 5 shows one example of the printer engine of the image forming apparatus employing the above-described image processing device 1.

The printer engine performs image formation (printing processing) by a predetermined form such as an electrophotographic form according to the drawing data

0015360.072701

(bitmap data) and control signal. For this purpose, the printer engine includes, in the case of the electrophotographic form, necessary components (not shown in the figure) for printing an image onto a recording paper based on the drawing data such as a photosensitive body 102, an optical writing unit 101, a development unit 103, a charging unit (not shown in the figure), a clearing unit (not shown in the figure) and so forth.

10                There, the optical writing unit 101 is operated according to the drawing data and control signal, an electrostatic latent image is thereby formed on the photosensitive body 102, and the development unit 103 develops the latent image by supplying a toner onto  
15 the photosensitive body 102 so as to form a toner image thereon. Then, the printer engine feeds a recording paper from a paper feeding unit 104 between the photosensitive body 102 and a transfer unit 105, transfers the toner image on the photosensitive body 102  
20 onto the recording paper, conveys the recording paper having the toner image transferred thereonto to a fixing part 106, which then fixes the toner image onto the recording paper. Thus, the image is printed.

                 Functions of the above-described image  
25 processing device 1 will now be described, with

0915360-072701

reference to FIG. 4.

As described above, the image processing device 1 analyses image drawing instructions given by the host apparatus 10 (in a step S1), determines (in a step S2) whether to causes the image production processing parts 6a through 6n to perform them separately after dividing the image drawing instructions into a plurality of sets of image drawing instructions, or to cause the image production processing parts 6a through 6n (or an appropriate one thereof) to perform them collectively without dividing the image drawing instructions into a plurality of sets of image drawing instructions. Thus, high-speed image drawing processing can be achieved.

Specifically, the host apparatus 10, based on instructions by a user, produces image drawing instructions through the image drawing instruction producing part 11, and transmits them to the printer which employs the image processing device 1. In this occasion, the image drawing instruction producing part 11 of the host apparatus 10 compresses an image object by a predetermined compressing method such as a fixed length compressing method, and, then, transmits it to the printer or the like.

The host I/F 2 of the image processing device

09915360.072701

1 receives the image drawing instructions transmitted  
from the host apparatus 10 through the communication  
circuit 8, and writes them into the memory 3. The  
instruction dividing and distributing part 4 reads the  
5 image drawing instructions from the memory 3, analyses  
the read image drawing instructions (in the step S1),  
determines (in the step S2) whether to process (in a  
step S4) these instructions separately after dividing  
(in a step S3) into a plurality of sets of instructions  
10 or to process (in a step S6) them collectively without  
dividing into a plurality of sets of instructions, and  
transfers the image drawing instructions to the  
plurality of image production processing parts 6a  
through 6n, which then generate bitmap data which is  
15 drawing data.

Specifically, the instruction dividing and  
distributing part 4 determines (in the step S2) whether  
or not the image drawing instructions read from the  
memory 3 are instructions for image processing  
20 concerning an image object, and, an area to be processed  
or a data amount of the corresponding image object is  
larger than the predetermined reference value. When the  
image drawing instructions read from the memory 3 are  
instructions for processing concerning an image object,  
25 and, an area to be processed or a data amount of the

00015360.072701

corresponding image object is larger than the  
predetermined reference value (Yes in the step S2), the  
image drawing instructions are divided into four sets of  
image data corresponding to the given image drawing  
5 instructions as shown in FIG. 2 (in the step S3), and  
the thus-divided image drawing instructions are then  
distributed into the respective image production  
processing parts 6a through 6n, which then process the  
divided sets of image drawing instructions (image data),  
10 respectively.

As the image object is one transmitted after  
being compressed by the host apparatus 10 by the fixed  
length compressing method, for example, as mentioned  
above, the instruction dividing and distributing part 4  
15 can easily calculate a position at which image data  
corresponding to each region obtained through the  
division is located in the image drawing instructions.  
Accordingly, as shown in FIG. 3, it is easy to produce  
image objects corresponding to the respective sets of  
20 image drawing instructions (image data) obtained through  
the division. Specifically, as shown in FIG. 3, the  
data part of the received image drawing instructions is  
divided into a plurality of data parts, while the header  
part of the received image drawing instructions is used  
25 for each of the thus-obtained plurality of data parts.

00015360.072701

Thus, it is easy to produce the plurality of sets of image drawing instructions.

For example, assuming that relevant image data (image drawing instructions) is such that each dot of gray scale is expressed by 1 byte, in a case where the image data has been compressed by a fixed length compressing method such that the thus-compressed image data can be decompressed while each line of the image data does not need any other lines of the image data for decompression, data at the left end (0, y) on any line y is located at a position obtained by an address expressed by the following formula:

$$\text{Head} + y \times \text{Width} \times \text{Ratio (bytes)}$$

where:

x denotes x coordinate (dots);

y denotes y coordinate (dots);

'Head' denotes the size of the header part (bytes);

'Width' denotes the lateral width of the image (dots/pixels);

'Height' denotes the height of the image (dots/pixels);

'Ratio' denotes the compression rate of the

0015366 072701

data part other than the header part;

the image data is arranged in the following  
order:

5           (0,0), (1,0), ..., (Width-1,0), (0,1), ...,  
(Width-1, Height-1)

and;

Width  $\times$  Ratio is an integer.

10           Such a method of fixed length compression is  
disclosed by Kenichiro Oka, Takeshi Agui and Masayuki  
Nakajima, in an article titled 'Image Coding Schemes for  
Hard Copies' of a journal of Japan Printing Society, Vol.  
27, No. 3, 1990, item 2.5, 'Proposal of GBTC  
15 (Generalized Block Truncation Coding)', for example.

In this example, bit data of 8 bits for each  
color of R, G and B for each pixel comes to be expressed  
by 72 bits for one block of  $4 \times 4$  pixels. As the data  
amount before the compression is  $8 \times 3 \times 4 \times 4 = 384$   
20 bits, the compression ratio (Ratio) is  $72/384$ . In this  
case, assuming that coordinate is counted from 0, data  
at the coordinate (0, y) is present at a location at the  
following address:

25           Head + (y  $\times$  Width)  $\times$  (72/384)

00015360.072701  
10/2/2009 09:55:40



where it is assumed that each of y and Width is a multiple of 4.

The respective image production processing part 6a through 6n analyze the divided sets of image drawing instructions given by the instruction driving and distributing part 4, generate bitmap data which can be processed by the printer engine, and transfers (in a step S5) it to the printer engine through the engine I/F 5.

10           The printer engine performs image formation by a predetermined form such as an electrophotography form, as described above, according to the drawing data (bitmap data) and control signal given by the image processing device 1.

15           When the image drawing instructions read from the memory 3 are instructions for processing concerning an image object, but, an area to be processed or a data amount of the corresponding image object is not larger than the predetermined reference value (No of the step 20 S2), the image drawing instructions are not divided, and the image drawing instructions are given to the image production processing parts 6a through 6n (or an appropriate one thereof) as they are.

          The respective image production processing 25 part 6a through 6n (or the appropriate one) analyze the

0015360-072701

not divided image drawing instructions given by the instruction driving and distributing part 4, generate bitmap data which can be processed by the printer engine (in the step s6), and transfers it to the printer engine through the engine I/F 5 (in a step S7). The printer engine performs image formation by the predetermined form such as an electrophotography form according to the drawing data (bitmap data) and control signal given by the image processing device 1.

10           In the above-described embodiment, the image data which is obtained through a fixed length compressing method such that decompression can be performed without need of any other line of image data. However, similarly, the present invention may also be  
15   applied to image data which is obtained through a data compressing method other than the fixed length compressing method.

For example, with regard to image data obtained through a variable length compressing method,  
20   it is possible to easily divide given image drawing instructions into a plurality of sets of image drawing instructions, each set of which can be decompressed without referring to any other set thereof, by holding a table by which, for partial coordinates of image, it is  
25   possible to know addresses at which pixel values

09915360-072701

corresponding to the coordinates are present.

For example, image data expressed in a manner such that each pixel along the gray scale is expressed by 1 byte is indicated by a pair of a pixel value of 1 byte and a pixel continuation number of 1 byte. Then, it is assumed that this image data is compressed by a run-length compression method (variable length compression method). It is assumed that the pixel continuation number is calculated independently for each line. In this case, for example, the following image data of  $12 \times 4$  pixels in hexadecimal notation:

7F, 7F, 7F, 7F, 80, 80, 80, 81, 80, 80, 7E, 7E  
7E, 7F, 7F, 80, 80, 80, 81, 81, 81, 80, 80, 80  
15 7E, 7F, 7F, 80, 80, 81, 82, 82, 82, 80, 80, 80  
7F, 7F, 7F, 7F, 80, 80, 82, 82, 82, 82, 81, 81

is compressed into the following data rows in hexadecimal notation:

20 7F, 04, 80, 03, 81, 01, 80, 02, 7E, 02  
7E, 01, 7F, 02, 80, 03, 81, 03, 80, 03  
7E, 01, 7F, 02, 80, 02, 81, 01, 82, 03, 80, 03  
25 7F, 04, 80, 02, 82, 04, 81, 02

00915360.072701

In this occasion, it is possible to properly divide the data on the compressed state in line units easily, by having the following table as the header part:

5        line:address  
         0:0  
         1:10  
         2:20  
         3:32

10

where the value of the address means the address of the image data at which the pixel value of the first pixel on the line is present.

Further, with regard to image data obtained  
15 through a compressing method such as MR coding such that two lines or four lines are regarded as one data block, and each data block can be decompressed without referring to any other data block, it is possible to easily divide given image drawing instructions into a  
20 plurality of sets of image drawing instructions, each set of which can be decompressed without referring to any other set thereof, by performing the division in a manner such that the unit of division includes a number of lines which is a multiple of two or four accordingly.

25

Thus, according to the image processing device

2025 RELEASE UNDER E.O. 14176

1 in the embodiment of the present invention, the  
instruction dividing and distributing part 4 analyzes  
given image drawing instructions obtained through data  
compression by a predetermined compressing method,  
5 divides image data corresponding to the image drawing  
instructions into a plurality sets of image drawing  
instructions, and distributes them to the plurality of  
image production processing parts 6a through 6n, which  
then generate drawing data for drawing processing from  
10 the image data corresponding to the image drawing  
instructions according to the plurality sets of image  
drawing instructions, respectively. In this occasion,  
the instruction dividing and distributing part 4 divides  
the given image drawing instructions into the plurality  
15 of sets of image drawing instructions without previously  
decompressing them, each set of image drawing  
instructions can be decompressed without referring to  
any other set of image drawing instructions.

Accordingly, compressed image data  
20 corresponding to given image drawing instructions is  
divided into a plurality of sets of image data without  
previously decompressing it. Thus, it is possible to  
achieve high-speed image processing with a reduced cost.

In this occasion, assuming that image data to  
25 be processed is image data obtained through data

compression by a compressing method such that the image data includes a plurality of data blocks, and each block can be decompressed without referring to any other data block, the image data can be easily divided into

5 divisions of image drawing instructions without decompressing it in a manner such that each division of image drawing instructions can be interpreted without referring to any other division of image drawing instructions. In this occasion, the image data may be

10 divided by a border between data blocks.

Further, by employing a fixed length compression method as mentioned above, it is very easy to divide image data of given image drawing instructions into divisions which can be processed by a plurality of

15 image production processing parts as they are in parallel. Accordingly, it is possible to further improve the image processing speed and reduce the costs therefor.

Further, in the embodiment shown in FIG. 1, it

20 is possible that a given set of image drawing instructions is divided into a number of divisions which is equal to or less than the number of image production processing parts which are on standby without performing image production processing.

25 Further, the present invention is not limited

0015360.072701

to the above-described embodiments, and variations and modifications may be made without departing from the scope of the present invention.

The present application is based on Japanese  
5 priority application No. 2000-241426, filed on August 9, 2000, the entire contents of which are hereby incorporated by reference.

09915360.072701